



BLASTWIZARD® KWIKBLAST 60

Includes a 20m blast hose and nozzle

The Blastwizard® Kwikblast 60 is possibly the most versatile system in the Blastwizard® Kwikblast range. Nifty and powerful – the Blastwizard® Kwikblast 60 is extremely portable with a blasting time of up to 3 hours before it requires refilling.

The Blastwizard® Kwikblast 60 is popular with the offshore industry where it is flown across the globe to carry out surface preparation on helipads, completions and oil and gas tubulars, spot repairs for maintenance programmes and coating removal as part of NDT preparation. The Blastwizard® Kwikblast 60 is also widely used by the shipping industry during voyages to carry out maintenance work as ships transport cargo around the world's waters.

Dimensions

Height	1070mm
Width	620mm
Depth	730mm
Unladen Weight	138kg
Laden Weight	269kg (garnet)

Specifications

Water Pressure & Flow	Standard tap pressure & flow
Water Consumption	100 – 150ml per minute
Grit Type	Standard particle blast media
Grit Consumption	0.6 – 1kg per minute
Blasting Time	Up to 3 hrs between refills
Air Supply	90 – 250cfm
Air Supply Hose	¾ or 2 inch
Blast Hose Size	1 inch
Blast Hose Max Length	100m
Blasting Pressure	20 – 100psi

Blast Media

Garnet – 4 bags
Iron Silicate – 3 bags
Glass – 2 bags

Straaltechniek International Group.

E-mail: info@straaltechniek.net **Website:** www.straaltechniek.net.

No rights can be derived from the content of this publication. Unless otherwise agreed upon in writing, all products and technical advice given are subject to our standard conditions of sale, available on our website www.straaltechniek.net. All rights reserved.

