



BLASTWIZARD® KWIKBLAST 60T

Include 145 cfm compressor

The self-contained Blastwizard® Kwikblast 60T is the most convenient system in the Blastwizard® Kwikblast range. It comprises of a Blastwizard® Kwikblast 60, a 115 litre water tank and a compressor of 90 or 140cfm — with a blasting time of up to 3 hours. In short: everything customers need to start blasting almost immediately.

The Blastwizard® Kwikblast 60 Trailer takes away the hassle and worry of being held up on site waiting for plant hire companies to deliver compressors and of potentially unreliable water supplies.

Dimensions

Height	1530mm
Width	2000mm
Depth	3050mm
Unladen Weight	1026kg
Laden Weight	1240kg (garnet)

Specifications

Water Tank	115 litres
Water Consumption	100 – 150ml per minute
Grit Type	Standard particle blast media
Grit Consumption	0.6 – 1kg per minute
Blasting Time	Up to 3 hrs between refills
Air Supply	90 – 140cfm
Air Supply Hose	¾ inch
Blast Hose Size	1 inch
Blast Hose Max Length	80m
Blasting Pressure	20 – 100psi
Compressor Fuel Tank	50 litres

Blast Media

Garnet – 8 bags
Iron Silicate – 7 bags
Glass – 5 bags

Straaltechniek International Group.

E-mail: info@straaltechniek.net Website: www.straaltechniek.net.

No rights can be derived from the content of this publication. Unless otherwise agreed upon in writing, all products and technical advice given are subject to our standard conditions of sale, available on our website www.straaltechniek.net. All rights reserved.

