



BLASTWIZARD® KWIKBLAST 200 ATEX

Includes a 20m blast hose and nozzle

Formidable, efficient and effective — the Blastwizard® Kwikblast 200 ATEX is the most powerful ATEX-certified system in the Blastwizard® Kwikblast range. Certified to CE EX II 2G EXh IIC T4 Gb, the Blastwizard® Kwikblast 200 ATEX is approved for use in environments containing hydrogen, acetylene or gases and vapours of equivalent hazard — including live hydrogen plants. With a blasting time of up to 18 hours, the Blastwizard® Kwikblast 200 ATEX is ideally suited for large-scale projects in hazardous conditions.

The extra-large 230 litre vessel capacity allows for up to 18 hours between refills, making the Blastwizard® Kwikblast 200 IIC T4 ideally suited for large-scale blasting projects in demanding and hazardous conditions.

Dimensions

Height	1280mm
Width	670mm
Depth	1020mm
Unladen Weight	209kg
Laden Weight	584kg (garnet)

Specifications

Water Pressure & Flow	Standard tap pressure & flow
Water Consumption	150 – 250ml per minute
Grit Type	Standard particle blast media
Grit Consumption	0.3 – 0.8kg per minute
Blasting Time	Up to 18 hrs between refills
Air Supply	250 – 400cfm
Air Supply Hose	¾ or 2 inch
Blast Hose Size	1 or 1¼ inch
Blast Hose Max Length	up to 250m
Blasting Pressure	20 – 120psi
ATEX Classification	CE EX II 2G EXh IIC T4 Gb

Blast Media

Garnet – 15 bags
Iron Silicate – 11 bags
Glass – 9 bags

Straaltechniek International Group.

E-mail: info@straaltechniek.net **Website:** www.straaltechniek.net.

No rights can be derived from the content of this publication. Unless otherwise agreed upon in writing, all products and technical advice given are subject to our standard conditions of sale, available on our website www.straaltechniek.net. All rights reserved.

